

# MB15

SURFACE




## MONOLINE-MB15

A surface mounted extruded aluminium profile manufactured from high-density aluminium with powder coated (white, grey or black) finish. Available with an opal domed diffuser for wide distribution.


MONOFLEX LED available in static white, tunable white and dynamic colour changing, with a choice of Nichia, Osram or Lumileds LED.

## TECHNICAL

|                         |                             |
|-------------------------|-----------------------------|
| <b>Housing:</b>         | Anodised Aluminium          |
| <b>Diffuser:</b>        | Polycarbonate UV Stabilised |
| <b>Lengths:</b>         | 3000mm                      |
| <b>Max LED Wattage:</b> | 24w/m                       |
| <b>Max PCB Width:</b>   | 12mm                        |
| <b>Hot-Spot Free:</b>   | ≥112 LED/m                  |
| <b>Weight:</b>          | 0.16kg/m                    |
| <b>IP Rating:</b>       | IP40                        |




## FINISH




## CATALOGUE NO.

|                    |                                      |
|--------------------|--------------------------------------|
| <b>MB15-W-3-OC</b> | 3000mm matt white with opal diffuser |
| <b>MB15-B-3-OC</b> | 3000mm matt black with opal diffuser |
| <b>MB15-A-3-OC</b> | 3000mm aluminium with opal diffuser  |


## ACCESSORIES



▮ **MB15-EC** 1 end cap



▮ **MB15-LC** 1 connector every 3 metres



▮ **MB15-MB** 1 bracket every metre (2 min)