

MD12

SURFACE



MONOLINE-MD12

A surface mounted linear LED luminaire designed for two lines of Monoflex LED, with 2-way light distribution. Manufactured from extruded anodised aluminium, finished in white or black, with opal diffusers. Suitable for surface mounting via concealed sprung metal fixing clips.

Each PCB module has an on-board Integrated Controller (IC), for precise constant current control, whilst a Schottky diode provides reverse polarity protection.

A range of LED options are available with a choice of Nichia, Osram or Lumileds LED, with colour temperatures from 2000K - 6500K and power outputs from 2 x 4.8W/m 2 x 14.4W/m.


Available in six standard lengths: 450mm, 950mm, 1450mm, 1950mm, 2450mm & 2950mm, which can be cut at 62.5mm intervals. Custom sizes also available upon request.



TECHNICAL

Input voltage:	24VDC [22.5~25VDC]
Current control:	On-board integrated controller (IC)
Reverse voltage protection:	On-board Schottky diode
Operating temperature (Ta):	-35 °C ~ 50 °C
PCB Temperature (Tc max):	<75 °C
Dimmable:	PWM (0/1-10V, DALI, DMX, TRIAC, ELV)
Ingress protection:	IP40

FINISH



MD12

SURFACE



PRODUCT CODE EXAMPLE


PROFILE	COLOUR	DIFFUSER	PCB	WATTAGE	SPECTRUM	LENGTH
MD12	- W	- OC	- D112	/ 9	- D4-827	- L4

SPECIFICATION


Profile	Colour	Diffuser	PCB	Wattage	Spectrum	Standard Lengths																																																												
	W White B Black	OC Opal	D112	4T 2 x 4.8w/m 9T 2 x 9.6w/m 14T 2 x 14.4w/m	<table border="1"> <tr><td>D4-827</td><td>Osram</td><td>2700K ≥Ra80</td></tr> <tr><td>D4-927</td><td>Lumileds</td><td>2700K ≥Ra90</td></tr> <tr><td>D4-830</td><td>Osram</td><td>3000K ≥Ra80</td></tr> <tr><td>D4-930</td><td>Lumileds</td><td>3000K ≥Ra90</td></tr> <tr><td>D4-835</td><td>Osram</td><td>3500K ≥Ra80</td></tr> <tr><td>D4-935</td><td>Lumileds</td><td>3500K ≥Ra90</td></tr> <tr><td>D4-840</td><td>Osram</td><td>4000K ≥Ra80</td></tr> <tr><td>D4-940</td><td>Lumileds</td><td>4000K ≥Ra90</td></tr> <tr><td>D4-850</td><td>Osram</td><td>5000K ≥Ra80</td></tr> <tr><td>D4-950</td><td>Lumileds</td><td>5000K ≥Ra90</td></tr> <tr><td>D4-857</td><td>Osram</td><td>5700K ≥Ra80</td></tr> <tr><td>D4-957</td><td>Lumileds</td><td>5700K ≥Ra90</td></tr> <tr><td>D4-865</td><td>Osram</td><td>6500K ≥Ra80</td></tr> <tr><td>D4-965</td><td>Lumileds</td><td>6500K ≥Ra90</td></tr> </table>	D4-827	Osram	2700K ≥Ra80	D4-927	Lumileds	2700K ≥Ra90	D4-830	Osram	3000K ≥Ra80	D4-930	Lumileds	3000K ≥Ra90	D4-835	Osram	3500K ≥Ra80	D4-935	Lumileds	3500K ≥Ra90	D4-840	Osram	4000K ≥Ra80	D4-940	Lumileds	4000K ≥Ra90	D4-850	Osram	5000K ≥Ra80	D4-950	Lumileds	5000K ≥Ra90	D4-857	Osram	5700K ≥Ra80	D4-957	Lumileds	5700K ≥Ra90	D4-865	Osram	6500K ≥Ra80	D4-965	Lumileds	6500K ≥Ra90	L1 450mm L2 950mm L3 1450mm L4 1950mm L5 2450mm L6 2950mm																		
D4-827	Osram	2700K ≥Ra80																																																																
D4-927	Lumileds	2700K ≥Ra90																																																																
D4-830	Osram	3000K ≥Ra80																																																																
D4-930	Lumileds	3000K ≥Ra90																																																																
D4-835	Osram	3500K ≥Ra80																																																																
D4-935	Lumileds	3500K ≥Ra90																																																																
D4-840	Osram	4000K ≥Ra80																																																																
D4-940	Lumileds	4000K ≥Ra90																																																																
D4-850	Osram	5000K ≥Ra80																																																																
D4-950	Lumileds	5000K ≥Ra90																																																																
D4-857	Osram	5700K ≥Ra80																																																																
D4-957	Lumileds	5700K ≥Ra90																																																																
D4-865	Osram	6500K ≥Ra80																																																																
D4-965	Lumileds	6500K ≥Ra90																																																																
			N112	4T 2 x 4.8w/m 9T 2 x 9.6w/m 14T 2 x 14.4w/m	<table border="1"> <tr><td>N4-820</td><td>Nichia</td><td>4000K ≥Ra80</td></tr> <tr><td>N4-920</td><td>Nichia</td><td>4000K ≥Ra90</td></tr> <tr><td>N4-822</td><td>Nichia</td><td>2200K ≥Ra80</td></tr> <tr><td>N4-922</td><td>Nichia</td><td>2200K ≥Ra90</td></tr> <tr><td>N4-825</td><td>Nichia</td><td>2500K ≥Ra80</td></tr> <tr><td>N4-925</td><td>Nichia</td><td>2500K ≥Ra90</td></tr> <tr><td>N4-827</td><td>Nichia</td><td>2700K ≥Ra80</td></tr> <tr><td>N4-927</td><td>Nichia</td><td>2700K ≥Ra90</td></tr> <tr><td>N4-830</td><td>Nichia</td><td>3000K ≥Ra80</td></tr> <tr><td>N4-930</td><td>Nichia</td><td>3000K ≥Ra90</td></tr> <tr><td>N4-835</td><td>Nichia</td><td>3500K ≥Ra80</td></tr> <tr><td>N4-935</td><td>Nichia</td><td>3500K ≥Ra90</td></tr> <tr><td>N4-840</td><td>Nichia</td><td>4000K ≥Ra80</td></tr> <tr><td>N4-940</td><td>Nichia</td><td>4000K ≥Ra90</td></tr> <tr><td>N4-850</td><td>Nichia</td><td>5000K ≥Ra80</td></tr> <tr><td>N4-950</td><td>Nichia</td><td>5000K ≥Ra90</td></tr> <tr><td>N4-857</td><td>Nichia</td><td>5700K ≥Ra80</td></tr> <tr><td>N4-957</td><td>Nichia</td><td>5700K ≥Ra90</td></tr> <tr><td>N4-865</td><td>Nichia</td><td>6500K ≥Ra80</td></tr> <tr><td>N4-965</td><td>Nichia</td><td>6500K ≥Ra90</td></tr> </table>	N4-820	Nichia	4000K ≥Ra80	N4-920	Nichia	4000K ≥Ra90	N4-822	Nichia	2200K ≥Ra80	N4-922	Nichia	2200K ≥Ra90	N4-825	Nichia	2500K ≥Ra80	N4-925	Nichia	2500K ≥Ra90	N4-827	Nichia	2700K ≥Ra80	N4-927	Nichia	2700K ≥Ra90	N4-830	Nichia	3000K ≥Ra80	N4-930	Nichia	3000K ≥Ra90	N4-835	Nichia	3500K ≥Ra80	N4-935	Nichia	3500K ≥Ra90	N4-840	Nichia	4000K ≥Ra80	N4-940	Nichia	4000K ≥Ra90	N4-850	Nichia	5000K ≥Ra80	N4-950	Nichia	5000K ≥Ra90	N4-857	Nichia	5700K ≥Ra80	N4-957	Nichia	5700K ≥Ra90	N4-865	Nichia	6500K ≥Ra80	N4-965	Nichia	6500K ≥Ra90	Cuttable at 62.5mm intervals
N4-820	Nichia	4000K ≥Ra80																																																																
N4-920	Nichia	4000K ≥Ra90																																																																
N4-822	Nichia	2200K ≥Ra80																																																																
N4-922	Nichia	2200K ≥Ra90																																																																
N4-825	Nichia	2500K ≥Ra80																																																																
N4-925	Nichia	2500K ≥Ra90																																																																
N4-827	Nichia	2700K ≥Ra80																																																																
N4-927	Nichia	2700K ≥Ra90																																																																
N4-830	Nichia	3000K ≥Ra80																																																																
N4-930	Nichia	3000K ≥Ra90																																																																
N4-835	Nichia	3500K ≥Ra80																																																																
N4-935	Nichia	3500K ≥Ra90																																																																
N4-840	Nichia	4000K ≥Ra80																																																																
N4-940	Nichia	4000K ≥Ra90																																																																
N4-850	Nichia	5000K ≥Ra80																																																																
N4-950	Nichia	5000K ≥Ra90																																																																
N4-857	Nichia	5700K ≥Ra80																																																																
N4-957	Nichia	5700K ≥Ra90																																																																
N4-865	Nichia	6500K ≥Ra80																																																																
N4-965	Nichia	6500K ≥Ra90																																																																

Other colour temperatures, tunable white, RGB and RGBW available upon request.


ACCESSORIES



MD12-EC Aluminium end cap



MD12-MB Mounting bracket 2 every 1 metres



MD12-LC Linear connector

Disclaimer:

Technical data is subject to change without prior notice. The data provide represent typical values. Due to tolerances in the production of components and binning of LEDs, values for lumen output (Lm), colour temperature (CCT) and power (W/m) can vary up to 10%. Electrical and thermal variation also influences the performance characteristics of LEDs