




MONOLINE-XS2

A surface mounted extruded aluminium profile manufactured from high-density aluminium, with a highly durable anodised finish and opal diffuser.


MONOFLEX LED is available in static white or tunable white, with a choice of Nichia, Osram and Lumileds LED.

TECHNICAL

Housing:	Anodised Aluminium
Diffuser:	PMMA
Lengths:	2000mm & 3000mm
Max LED Wattage:	14.4w/m
Max PCB Width:	8mm
Hot-Spot Free:	≥112 LED/m
Weight:	0.1kg/m
IP Rating:	IP40




FINISH




CATALOGUE NO.

XS2-2-OC	2000mm anodised silver with opal diffuser
XS2-3-OC	3000mm anodised silver with opal diffuser

ACCESSORIES



XS2-SMB Sprung steel bracket



XS2-EC Aluminium end cap


MONOFLEX-PRO




Our professional-grade flexible LED tapes are manufactured in Europe using high-quality components from leading manufacturers.

Our Pro range (N-series) incorporates industry-leading LEDs from Nichia, providing exceptional performance: colour rendering, colour appearance, colour consistency, lumen output, and lumen maintenance.

N112



N120





N175



NV70



NV112





RGB48



RGB96



RGBW




MONOFLEX-ECO




Our professional-grade flexible LED tapes are manufactured in Europe using high-quality components from leading manufacturers.

Our Eco range (D-series) features the PCB and electronic components of our Pro range (N-series), except for the LEDs, which are either Osram or Lumileds, depending on the colour temperature and colour rendering index.

D112



D120



D175



DV70



Disclaimer: Technical data is subject to change without prior notice. The data provided represent typical values. Due to tolerances in the production of components, and binning of LEDs, values for lumen output (Lm) and power (W/m) can vary by up to +/- 10%, whilst the colour temperature (CCT) can vary +/- 100°K. Electrical and thermal variation also influences the performance characteristics of LEDs.