



Cube-duo round LED

IP 40

Apparecchio a plafone a LED, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood), orientabilità +/- 15°.

Fixture-mounted unit, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood), not adjustable.

2 nero
black

4 bianco
white

321.0020.01.20-- 2 4
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,



321.0020.01.40-- 2 4
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,
cod. 321.0020.01.X.2700-- per 2700°K
cod. 321.0020.01.X.4000-- per 4000°K



Cube-duo square LED

IP 40

Apparecchio a plafone a LED, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood), orientabilità +/- 15°.

Fixture-mounted unit, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood), adjustability +/-15°.

321.0021.01.20-- 2 4
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,



321.0021.01.40-- 2 4
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,
cod. 321.0021.01.X.2700-- per 2700°K
cod. 321.0021.01.X.4000-- per 4000°K

