



Kors, led 6w



Incasso trimless a LED, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood), non orientabile.

Recessed trimless LED fixture, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood), not orientable.

1917.0035.01.20.-- 2 
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,

1917.0035.01.40.-- 2 
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,

cod. 1917.0035.01.2700.**-- per 2700°K
cod. 1917.0035.01.4000.**-- per 4000°K


ATTENZIONE: applicabile solo con cartongesso standard spessore 12mm.
ATTENTION: applicable only with standard 12mm plasterboard.

Kors, led 9w



Incasso trimless a LED, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood), non orientabile.

Recessed trimless LED fixture, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood), not orientable.

1917.0035.02.20.-- 2 
9w, 3000°K, 1025lm, 114lm/w, CRI>90,

1917.0035.02.34.-- 2 
9w, 3000°K, 1025lm, 114lm/w, CRI>90,

cod. 1917.0035.02.2700.(X°).-- per 2700°K
cod. 1917.0035.02.4000.(X°).-- per 4000°K


kors, 9w DALI

1917.0035.08.(°K).(X°).--
9w, 1025lm, 114lm/w, CRI>90,

kors, spot led 9w without driver



Driver da aggiungere separatamente.
Drivers to be added separately.

1917.0035.03.(°K).(X°).-- 2 
Max 9w, CRI>90, max 500mA,

ATTENZIONE: applicabile solo con cartongesso standard spessore 12mm.
ATTENTION: applicable only with standard 12mm plasterboard.

2 nero
black