



Mico 48v, proiettore track



Proiettore LED con adattatore meccanico a binario 48V, con elettronica step-down 48v, 500mA, gradi di emissione 14, 25°, 35° orientabilità +/-90°.

Projector LED with a mechanical track adapter for 48V, with step-down 48v-500mA, emission degrees 14°, 25°, 35° adjustability +/-90°.

139.0048.14.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



139.0048.25.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



139.0048.35.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



cod. 139.0048.X.2700.-- per 2700°K
cod. 139.0048.X.4000.-- per 4000°K

2 tutto nero
all in black

4 cornice bianca + interno nero
white frame + black inside

Mico 48v, proiettore track DALI



Proiettore LED con adattatore meccanico a binario 48V, con elettronica step-down 48v, 500mA, gradi di emissione 14, 25°, 35° orientabilità +/-90°.

DALI Projector LED with a mechanical track adapter for 48V, with step-down 48v-500mA, emission degrees 14°, 25°, 35° adjustability +/-90°.

139.0048.01.14.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



139.0048.01.25.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



139.0048.01.35.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



cod. 139.0048.X.2700.-- per 2700°K
cod. 139.0048.X.4000.-- per 4000°K

frangiluce a nido d'ape *honeycomb*

139.01 1 pc



schermo a croce *cross baffle*

139.02 1 pc

