



Mico proiettore incasso



Proiettore LED ad incasso, gradi di emissione 14°, 25°, 35° orientabilità +/-90° completo di alimentatore.

Recessed projector LED, emission degrees 14°, 25°, 35° adjustability +/-90° complete with power supply.

139.1002.02.14.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



139.1002.02.25.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



139.1002.02.35.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



cod. 139.1002.02.X.2700.-- per 2700°K
cod. 139.1002.02.X.4000.-- per 4000°K

2 tutto nero
all in black

4 cornice bianca + interno nero
white frame + black inside

Mico proiettore incasso DALI



Proiettore LED ad incasso, gradi di emissione 14°, 25°, 35° orientabilità +/-90° completo di alimentatore DALI.

Recessed projector LED, emission degrees 14°, 25°, 35° adjustability +/-90° complete with DALI power supply.

139.1002.08.14.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



139.1002.08.25.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



139.1002.08.35.-- 2 4
9w, 3000°K, 1200lm, 133lm/w, CRI>90,



cod. 139.1002.08.X.2700.-- per 2700°K
cod. 139.1002.08.X.4000.-- per 4000°K

frangiluce a nido d'ape
honeycomb

139.01 1 pc



schermo a croce
cross baffle

139.02 1 pc

