



## R\_50, led cob 6-9w



2 nero  
black

4 bianco  
white

Apparecchio ad incasso LED con cornice, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° spot, oppure 40° flood.

*Recessed LED fixture with frame, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° spot or 40° flood.*

**18.0008.01.20.--** 2 4  
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,



**18.0008.01.40.--** 2 4  
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,



cod. 18.0008.01.2700.(X°)-- per 2700°K  
cod. 18.0008.01.4000.(X°)-- per 4000°K

**18.0008.02.20.--** 2 4  
9w, 3000°K, 1025lm, 114lm/w, CRI>90,



**18.0008.02.34.--** 2 4  
9w, 3000°K, 1025lm, 114lm/w, CRI>90,



cod. 18.0008.02.2700.(X°) per 2700°K  
cod. 18.0008.02.4000.(X°) per 4000°K

## R\_50, 9w DALI

**18.0008.08.(°K).(X°)--**  
9w, 1025lm, 114lm/w, CRI>90,



## R\_50, spot led without driver

Driver da aggiungere separatamente.  
Drivers to be added separately.



**18.0008.03.(°K).(X°)--** 2 4  
max 9w, CRI>90, max 500mA,

