



Rc_110, led cob 9w



Apparecchio ad incasso LED trimless, completo di alimentatore e connessioni tolleranza colore 3 McAdams, gradi di emissione 25° (spot) oppure 35° (flood), con proiettore orientabile.

Recessed trimless LED fixture, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 25° (spot) or 35° (flood), with adjustable projector.

18.2010.02.20.-- 22 44 42 24
9w, 3000°K, 1025lm, 114lm/w, CRI>90,



18.2010.02.34-- 22 44 42 24
9w, 3000°K, 1025lm, 114lm/w, CRI>90,



cod. 18.2010.**.2700.(X°).-- per 2700°K

cod. 18.2010.**.4000.(X°).-- per 4000°K

22 incasso nero + proiettore nero
black trimless + black projector

44 incasso bianco + proiettore bianco
white trimless + white projector

42 incasso bianco + proiettore nero
white trimless + black projector

24 incasso nero + proiettore bianco
black trimless + white projector

RC_110, 9W DALI



18.2010.08.(°K).(X°).--

9w, 1025lm, 114lm/w, CRI>90,

RC 110, led without driver

Driver da aggiungere separatamente.

Drivers to be added separately.



18.2010.03.(°K).(X°).-- 22 44 42 24
Max 9w, CRI>90, max 500mA,



plaster kit / kit da stuccare

18.2008.PK plaster kit

frangiluce a nido d'ape
honeycomb

139.01 1 pc



schermo a croce
cross baffle

139.02 1 pc

