

RF_50, led cob 6-9w





2 nero
black

4 bianco
white

Apparecchio ad incasso LED senza cornice, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° spot, oppure 40° flood.

Recessed LED fixture without frame, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° spot or 40° flood.

18.1001.01.20.-- 2 4 
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,

18.1001.01.40.-- 2 4 
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,

cod. 18.1001.01.2700.X.-- per 2700°K
cod. 18.1001.01.4000.X.-- per 4000°K




18.1001.02.20.-- 2 4 
9w, 3000°K, 1025lm, 114lm/w, CRI>90,

18.1001.02.34.-- 2 4 
9w, 3000°K, 1025lm, 114lm/w, CRI>90,

cod. 18.1001.02.2700.(X°).-- per 2700°K
cod. 18.1001.02.4000.(X°).-- per 4000°K

RF_50, 9w DALI

18.1001.08.(°K).(X°).--  IP 40    
9w, 1025lm, 114lm/w, CRI>90,

RF_50, spot led without driver IP 40   
Driver da aggiungere separatamente.
Drivers to be added separately.

18.1001.03.(°K).(X°).-- 2 4 
Max 9w, CRI>90, max 500mA,

plaster kit / kit da stuccare

18.1001.PK plaster kit