



## RF\_70, led cob 6-9w

IP 40

2 nero  
black4 bianco  
white

Apparecchio ad incasso LED senza cornice, a scomparsa totale, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood), adjustability +/- 25°.

*Recessed LED fixture without frame and trimless, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood), adjustability +/- 25°.*

18.1002.01.20.-- 2 4  
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,



18.1002.01.40.-- 2 4  
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,



cod. 18.1002.01.2700.\*\*.-- per 2700°K  
cod. 18.1002.01.4000.\*\*.-- per 4000°K

18.1002.02.20.-- 2 4  
9w, 3000°K, 1025lm, 114lm/w, CRI>90,



18.1002.02.34.-- 2 4  
9w, 3000°K, 1025lm, 114lm/w, CRI>90,



cod. 18.1002.02.2700.(X°).-- per 2700°K  
cod. 18.1002.02.4000.(X°).-- per 4000°K

## RF\_70, 9w DALI

18.1002.08.(°K).(X°).--  
9w, 1025lm, 114lm/w, CRI>90,

## RF\_70, spot led without driver

Driver da aggiungere separatamente.  
Drivers to be added separately.

IP 40

18.1002.03.(°K).(X°).-- 2 4  
Max 9w, CRI>90, max 500mA,



## plaster kit / kit da stuccare

18.1002.PK plaster kit