



## Squa 50 filo 6w, cartongesso

IP 40

2 nero  
black

4 bianco  
white

Apparecchio ad incasso LED a filo muro, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood).

*Recessed trimless LED fixture, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood).*

1917.0009.01.20.-- 2 4  
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,



1917.0009.01.40.-- 2 4  
6w, 3000°K, 615lm, 102,5lm/w, CRI>90,



cod. 1917.0009.01.2700.\*\*.-- per 2700°K  
cod. 1917.0009.01.4000.\*\*.-- per 4000°K

## Squa 50 filo 9w, cartongesso

IP 40

Apparecchio ad incasso LED a filo muro, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood).

*Recessed trimless LED fixture, complete with driver and connections, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood).*

1917.0009.02.20.-- 2 4  
9w, 3000°K, 1025lm, 114lm/w, CRI>90,



1917.0009.02.34.-- 2 4  
9w, 3000°K, 1025lm, 114lm/w, CRI>90,



cod. 1917.0009.02.2700.(X°).-- per 2700°K  
cod. 1917.0009.02.4000.(X°).-- per 4000°K

## Squa 50 filo 9W, DALI

IP 40

1917.0009.08.(°K).(X°).--  
9w, 1025lm, 114lm/w, CRI>90,

## Squa 50 filo, frosted glass

1917.0010.AC vetro satinato / frosted glass