



## Tiny track, 48v



Proiettore LED con adattatore meccanico con elettronica step-down 48v 250mA, gradi di emissione 30°, 40°, 60°. Orientabile 360° - 80°.

LED projector with mechanical adaptor, with step-down 48v 250mA electronic, emission degrees 30°, 40°, 60°. Adjustability 360° - 80°.

**2014.0048.30--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



**2014.0048.40--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



**2014.0048.60--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



cod. 2014.0048.X.2700.-- per 2700°K

cod. 2014.0048.X.4000.-- per 4000°K

## Tiny track, 48v DALI



**2014.0048.08.30--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



**2014.0048.08.40--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



**2014.0048.08.60--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



cod. 2014.0048.08.X.2700.-- per 2700°K

cod. 2014.0048.08.X.4000.-- per 4000°K

## Tiny out for Dark, 48v



Proiettore LED con adattatore meccanico con elettronica step-down 48v 250mA, gradi di emissione 30°, 40°, 60°. Orientabile 360° - 80°.

LED projector with mechanical adaptor, with step-down 48v 250mA electronic, emission degrees 30°, 40°, 60°. Adjustability 360° - 80°.

**2014.0148.30--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



**2014.0148.40--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



**2014.0148.60--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



cod. 2014.0148.X.2700.-- per 2700°K

cod. 2014.0148.X.4000.-- per 4000°K

## Tiny out for dark, 48v DALI



**2014.0148.08.30--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



**2014.0148.08.40--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



**2014.0148.08.60--** 2 4 96

8,3W, 979 Lm, CRI> 90, 3000°K,



cod. 2014.0048.08.X.2700.-- per 2700°K

cod. 2014.0048.08.X.4000.-- per 4000°K

2 nero  
black

4 bianco  
white

96 bronzo + adattatore nero  
bronze + black adapter