

# MACROLUX

mx0\_45

Profiles - recessed



Colour: White (94)  
Diffuser: Opal | Prismatic  
IP: 40  
Class: Class III  
Type of recessed: Plasterboard  
Pieces: 1  
Length (mm): 3000



Conforms to European directives



Conforms to the ROHS directive



Insulation class





Type of disposal




Protection index







Article code	Article	Colour	Type of recessed	Diffuser	Length (mm)
1324.0045.00.94	MX0_45/DO-94 L=max 3m	White (94)	Plasterboard	Opal	
1324.0045.01.94	MX0_45/DO/3000-94 L=3m - EMPTY STANDARD	White (94)	Plasterboard	Opal	3000
1324.00459.00.94	MX0_45/DP-94 L=max 3 m	White (94)	Plasterboard	Prismatic	
1324.00459.01.94	MX0_45/DP/3000-94 L=3m - EMPTY STANDARD	White (94)	Plasterboard	Prismatic	3000




Article code	Name	Description	Watt (W)	Driver's type
1.024015	Driver LED 24V 15W IP20	Dimensioni 45 x 19 x 123 mm	15	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024020	Driver LED 24V 20W IP20	Dimensioni 36 x 16 x 103 mm	20	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024030	Driver LED 24V 30W IP20	Dimensioni 50 x 17 x 156 mm	30	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024050	Driver LED 24V 50W IP20	Dimensioni 59 x 29 x 167 mm	50	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024075	Driver LED 24V 75W IP20	Dimensioni 61 x 29 x 184 mm	75	On/Off




Article code	Name	Description	Watt (W)
1.97759	Driver LED 24V 150W IP67	Dimensioni 69 x 37 x 206 mm	150




Article code	Name	Description	Watt (W)
1.97745	Driver LED 24V 200W IP67	Dimensioni 69 x 37 x 206 mm	200



Article code	Name	Description	Colour
1324.5045.94	MO_45/TC-94	Testata di chiusura, finitura bianco - Compatibile con MXO_45 e MTO_45	White (94)
1324.5045.94.10	MO_45/TC-94 - 10 PZ	Testata di chiusura, finitura bianco - Compatibile con MXO_45 e MTO_45	White (94)



Article code	Name	Description
134.1145	M_45/GL	Staffa di giunzione lineare - Compatibile con MXO_45, MX1_45, MT1_45 e MD_45.
134.1145.10	M_45/GL - 10 PZ	Staffa di giunzione lineare - Compatibile con MXO_45, MX1_45, MT1_45 e MD_45.



Article code	Name	Description
1324.6045	MO_45/SA	Staffa ancoraggio / Bracket (1 pz.)

200 x 200

Powered by HTML.COM

Article code	Name	Description
1324.2045	MX0_45/G090	Connessione ad angolo orizzontale 90° / Horizontal connection corner 90°

200 x 200

Powered by HTML.COM

Article code	Name	Description
1324.3045	MX0_45/GV90	Connessione ad angolo verticale 90° / Vertical connection corner 90°

200 x 200

Powered by HTML.COM

Article code	Name	Description
1324.4045	MX0_45/GV270	Connessione ad angolo verticale 270° / Vertical connection corner 270°

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Length (mm)	Watt (W)
1324.17.500	M_45/500/10W/3000°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 3000°K - Lunghezza 500 mm   Driver escluso	3000	500	9

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.500.2700	M_45/500/10W/2700°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 2700°K - Lunghezza 500 mm   Driver escluso	2700	9	500

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.500.4000	M_45/500/10W/4000°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 4000°K - Lunghezza 500 mm   Driver escluso	4000	9	500

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.1000.2700	M_45/1000/20W/2700°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 2700°K - Lunghezza 1000 mm   Driver escluso	2700	18.5	1000

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.1000	M_45/1000/20W/3000°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 3000°K - Lunghezza 1000 mm   Driver escluso	3000	18.5	1000

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.1000.4000	M_45/1000/20W/4000°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 4000°K - Lunghezza 1000 mm   Driver escluso	4000	18.5	1000

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.1500.2700	M_45/1500/30W/2700°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 2700°K - Lunghezza 1500 mm   Driver escluso	2700	28	1500

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.1500	M_45/1500/30W/3000°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 3000°K - Lunghezza 1500 mm   Driver escluso	3000	28	1500

200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.1500.4000	M_45/1500/30W/4000°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 4000°K - Lunghezza 1500 mm   Driver escluso	4000	28	1500



200 x 200

Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.2000.2700	M_45/2000/40W/2700°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 2700°K - Lunghezza 2000 mm   Driver escluso	2700	9	2000

200 x 200


Powered by HTML.COM

Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.2000	M_45/2000/40W/3000°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 3000°K - Lunghezza 2000 mm   Driver escluso	3000	9	2000


200 x 200

Powered by HTML.COM


Article code	Name	Description	Light Temperature (°K)	Watt (W)	Length (mm)
1324.17.2000.4000	M_45/2000/40W/4000°K	Profilo alluminio interno "H" + LED 19.6W/m, 24V, 4000°K - Lunghezza 2000 mm   Driver escluso	4000	9	2000



Article code	Name	Description	Length (mm)
134.0145.01	M_45/H/3000 L=3m - EMPTY STANDARD	Profilo alluminio H interna, serie M45 - Senza taglio a misura	3000



Article code	Name	Description
1324.9145.01	M_45/Diffusore Opale L=3m - EMPTY STANDARD	Profilo PC Opale / Compatibile con MX_45, MT_45, MD_45, ML_45 - Senza taglio a misura



Article code	Name	Description
1324.91459.01	M_45/Diffusore Prismatico L=3m - EMPTY STANDARD	Profilo PC Prismatico / Compatibile con MX_45, MT_45, MD_45, ML_45 - Senza taglio a misura